

प्रति,

**विषय:- नविन जनरेटर रूम व क्वॉरीडोअरमधील मोकळ्या जागेत जनरेटर स्थलांतरीत करणेकामी
कॉक्रीट फाऊंडेशन तयार करणे व शेड उभारणी करणेकामी कोटेशन देणेबाबत.....**

नविन जनरेटर रूम व क्वॉरीडोअरमधील मोकळ्या जागेत जनरेटर स्थलांतरीत करणेकामी कॉक्रीटमध्ये फाऊंडेशन तयार करणे व शेड उभारणी करावयाचे आहे. तरी सदर कामाचे आपण आपले दरपत्रक (कोटेशन) देण्याचे करावे.

Sr No	Description	Quantity	Unit
1	Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 m. beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.5 m.) By Mechanical Means (21.02)	75.6	Cum
2	Providing dry/ trap/ granite/ quartzite/ gneiss rubble stone soling 15 cm to 20 cm thick including hand packing and compacting etc. complete.	14.63	Cum
3	Filling in plinth and floors with contractors material / brought from outside and approved by Engineer incharge in layers of 15 cm to 20 cm including watering and compaction etc.complete item no 21.37	18.81	Cum
4	Providing and laying Cast in situ/Ready Mix cement concrete in M10 of trap/ granite/quartzite/gneiss metal for foundation and bedding / steps including steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing etc. complete. The Cement Mortar 1:3 plaster is considered for rendering uneven and honeycombed surface, only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc. (Wooden centering will not be allowed.),with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade) (24.04)	2.84	Cum

Sr No	Description	Quantity	Unit
5	Providing and laying Cast in situ / Ready Mix cement concrete M-20 of trap / granite / quartzite / gneiss metal for R.C.C. work in foundations like raft, strip foundations, grillage and footings of R.C.C. columns and steel stanchions etc. columns as per detailed designs and drawing or as directed including steel centering, formwork, cover blocks, laying / pumping, compaction finishing the formed surfaces with cement mortar 1:3 of sufficient minimum thickness to give a soothan even surface or roughening if special finishis to be provided and curing etc. complete. (Excluding reinforcement and structural steel).with fully automatic micro process or based PLC with SCADA enabled reversible Drum Type mixer / concrete Batch mix plant (Panmixer) etc. complete. With fine aggregate (Crushed sand VSI Grade)	7.8	Cum
6	Providing and laying Cast in situ / Ready Mix cement concrete in M- 20 of trap / granite / quartzite / gneiss metal for R.C.C. pardi of required thickness including steel centering, formwork, cover blocks, laying / pumping, compacting, curing, finishing and roughening them if special finishis to be provided and curing complete. (Excluding reinforcement and structural steel). with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer / concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade)	5.744	Cum
7	Providing and laying Cast in situ / Ready Mix cement concrete in M15 of trap / granite / quartzite / gneiss metal for foundation / steps including steel centering, formwork, laying / pumping, compacting, roughening them if special finishis to be provided, finishing uneven and honey combed surface and curing etc. complete. The Cement Mortar 1:3 plaster is considered for rendering uneven and honeycombed surface, only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc. (Wooden centering will not be allowed.), with fully automatic microprocessor based PLC with SCADA enabled reversible Drum Type mixer / concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade)	4.385	Cum
8	Providing and laying Cast in situ / Ready Mix cement concrete in M20 of trap / granite / quartzite / gneiss metal for steps including steel centering, formwork, laying / pumping, compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing etc. complete. The Cement Mortar 1:3 plaster is considered for rendering uneven and honey combed surface, only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc. (Wooden centering will not be allowed.), with fully automatic micro processor based PLC with SCADA enabled reversible Drum Typemixer /concrete Batch mix plant (Panmixer) etc. complete. With fine aggregate (Crushed sand VSI Grade)	3.3	Cum
9	Providing and fixing in position TMT-FE-500 bar reinforcement of various diameters for R.C.C. pile caps , footings, foundations, slabs, beams columns, canopies, staircase, newels, chajjas, lintels pardis, copings, fins, arches etc. as per detailed designs, drawings and schedules. including cutting, bending, hooking the bars, binding with wires or tack welding and supporting as required complete.	0.395	MT
10	Providing internal cement plaster 20mm. thick in Single coats in cement mortar 1:3 without neeru finish, to concrete, brick surface, in all positions including scaffolding and curing etc. complete.- With water proffing Compound to avoid leakages- Deviated	5.94	sqm

Sr No	Description	Quantity	Unit
11	Providing, fabricating and erecting at site of work the tubular steel structure (shed) as per standard design and specifications having various spans in between trusses and in multiples of standard length of bays as specified as per standard specifications ,inclusive of cost of steel tubular trusses, tubular columns purlins, tie runners, foundation bolts, base plates, nuts and bolts, welding wherever required etc. as per detailed drawing inclusive of one coat of anticorrosive paint and two coats of oil painting of approved quality and shade etc. complete. Spec. One Number : As directed by Engineer-in-charge.	0.515	MT
12	Providing and fixing of colour coated Zinicaluminium (R) AZ 150 (min 150 gms/ sq.mt. total on each side)profiled sheets for roofing. The feed material is manufactured out of nominal 0.45mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min. 550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyster paint coat (with in organic pigment).The paint shall have a total coating thickness of nomina l35um, comprising of nominal 25 um exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950-1050 mm effectiv ecover width and nominal 25-30 mm deep ribs with subtle square fluting in the five panat nominal 180-250 mm center-to-center. Theen dribs hallbe designed for anti-capacity groove .and return leg. The feed material should have coilmanufacturers product details marked a regular interval. including fasteners with min. fastened with min.25 um Zinc- Tinalloy coated, Hexhead, self-drilling screw etc. complete. (weight of profile 4.5 2 Kilogram / OneSquare Metre) 900 mm girth (Surface Width).	51.85	sqm

तरी उपरोक्तप्रमाणे नविन जनरेटर रूम व क्वॉरीडोअरमधील मोकळ्या जागेत जनरेटर स्थलांतरीत करणेकामी कॉंक्रीटमध्ये फाऊंडेशन तयार करणे व शेड उभारणी करणेकामी आपण आपले सिलबंद कोटेशन खालील अटी व शर्तीस अधिन राहुन त्वरीत देणेचे करावे हि विनंती.

अटी व शर्ती:-

1. उपरोक्त दर हे सर्व करांसहीत देण्याचे करावे.
2. आपले दर मंजूर होताच उपरोक्तप्रमाणे काम त्वरीत पूर्ण करणे आपणावर बंधनकारक राहिल. मंजूर दरामध्ये कोणत्याही कारणास्तव दरवाढ मिळणार नाही.
3. सदर काम पूर्ण करण्याचा कालावधी 30 दिवस आहे.
4. कामाची बयाणा रक्कम रु ५०००/- मात्र आहे, कोटेशन सोबत बयाणा रक्कम भरल्याची संस्थानची पावती जोडावी.
5. सदरचे काम मुदतीत पूर्ण न केल्यास रु.५००/- प्रती दिवस या दराने विलंबापोटी दंड आकारणी करणेत येईल.
6. काम पूर्ण झालेनंतर प्रत्यक्ष मोजमापानुसार बील अदा करणेत येईल. कामापोटी अॅडव्हान्स दिला जाणार नाही.
7. सदर कोटेशन सिलबंद पाकिटात देऊन मा. मुख्य कार्यकारी अधिकारी, श्री साईबाबा संस्थान विश्वस्तव्यवस्था, शिर्डी यांचे नावे सादर करून कोटेशनवर कामाचे नावाचा उल्लेख करावा.

(बी.डी.दाभाडे)
कार्यकारी अभियंता,
श्री साईबाबा संस्थान विश्वस्तव्यवस्था, शिर्डी

